

Specifications

For other materials or modifications, please consult TESCOM.

OPERATING PARAMETERS

Pressure rating per criteria of ANSI/ASME B31.3

Maximum Inlet Pressures

- Air Loaded:** 450 psig / 31.0 bar
- Dome Loaded:** 1000 psig / 68.9 bar
- Spring Loaded:** 0-30 psig / 0-2.1 bar
- 0-80 psig / 0-5.5 bar
- 0-185 psig / 0-12.8 bar
- 0-300 psig / 0-20.7 bar
- 0-375 psig / 0-25.9 bar

Reference Pressure

- Air Loaded:** 150 psig maximum (3.1 ratio) / 10.3 bar
- Dome Loaded:** 1000 psig maximum / 68.9 bar

Design Proof Pressure

150% rated pressure

Leakage

Bubble-tight

Operating Temperature

See Part Number Selector

Flow Capacity

$C_v = 2.0$



DOME

SPRING

TESCOM 26-2700 Series is a high flow, low pressure backpressure regulator with spring, dome and air loading options.

MEDIA CONTACT MATERIALS

Seat, Main Valve

CTFE, Vespel® SP21

Body, Bonnet, Back Cap

Brass, 303 Stainless Steel, 316 Stainless Steel

O-Rings

Buna-N, E.P., Viton®

Diaphragm

Gylon®

Remaining Parts

300 Series Stainless Steel, Nitronic 60

OTHER

Cleaning

CGA 4.1 and ASTM G93

Weight (approximate)

10.5 lbs / 4.8 kg

Vespel® and Viton® are registered trademarks of E.I. du Pont de Nemours and Company.

Gylon® is a registered trademark of Garlock, Inc.


Applications

- Pump and compressor control
- Process pressure control
- High flow, low pressure chemical injection


Features and Benefits

- Gas or liquid service
- Dome and air actuated models are available
- Compatible with TESCOM ER3000 Electropneumatic Controllers
- High flow capabilities


26-2700 Series Regulator Drawing



Spring Load



Dome Load





Air Load

All dimensions are reference & nominal
Metric [millimeter] equivalents are in brackets

26-2700 Series Regulator Flow Charts

For more information on how to read flow curves, please refer to the Flow Curves and Calculations document (debul2007x012) in the TESCOM catalog or on www.tescom.com.



26-2700 Series Regulator Part Number Selector

Repair Kits, Accessories & Modifications may be available for this product. Please contact TESCOM for more information.

Example for selecting a part number:

Air Loaded

26-27 2 0 - V 2 08A

BASIC SERIES	BODY MATERIAL	MAXIMUM INLET PRESSURE	MATERIALS		OPERATING TEMPERATURE	INLET AND OUTLET PORT TYPE	INLET AND OUTLET PORT SIZE		
			O-RING	VALVE SEAT					
26-27	1 – Brass	0 – 450 psig 31.0 bar	B – BUNA-N	CTFE	-40°F to 165°F / -40°C to 74°C	1 – SAE	08 – 1/2"		
	2 – 303 Stainless Steel		E – E.P.	Vespel® SP21	-40°F to 165°F / -40°C to 74°C			2 – NPTF	12 – 3/4"
			M – E.P.	CTFE	-40°F to 165°F / -40°C to 74°C				
			V – Viton®	CTFE	0°F to 165°F / -18°C to 74°C				
			W – Viton®	Vespel® SP21	0°F to 300°F / -18°C to 149°C				

Dome Loaded

26-27 2 0 - V 2 08D

BASIC SERIES	BODY MATERIAL	MAXIMUM INLET PRESSURE	MATERIALS		OPERATING TEMPERATURE	INLET AND OUTLET PORT TYPE	INLET AND OUTLET PORT SIZE
			O-RING	VALVE SEAT			
26-27	1 – Brass	0 – 1000 psig 68.9 bar	E – E.P.	Vespel® SP21	-40°F to 165°F / -40°C to 74°C	1 – SAE	08 – 1/2"
	2 – 303 Stainless Steel		M – E.P.	CTFE	-40°F to 165°F / -40°C to 74°C		
			V – Viton®	CTFE	0°F to 165°F / -18°C to 74°C		
			W – Viton®	Vespel® SP21	0°F to 300°F / -18°C to 149°C		
6 – 316 Stainless Steel					2 – NPTF	12 – 3/4"	

Spring Loaded

26-27 2 2 - V 2 08S

BASIC SERIES	BODY MATERIAL	MAXIMUM INLET PRESSURE	MATERIALS		OPERATING TEMPERATURE	INLET AND OUTLET PORT TYPE	INLET AND OUTLET PORT SIZE		
			O-RING	VALVE SEAT					
26-27	1 – Brass	0 – 0-30 psig 0-2.1 bar	E – E.P.	Vespel® SP21	-40°F to 165°F / -40°C to 74°C	1 – SAE	08 – 1/2"		
	2 – 303 Stainless Steel	1 – 0-80 psig 0-5.5 bar	M – E.P.	CTFE	-40°F to 165°F / -40°C to 74°C			2 – NPTF	12 – 3/4"
			V – Viton®	CTFE	0°F to 165°F / -18°C to 74°C				
			W – Viton®	Vespel® SP21	0°F to 300°F / -18°C to 149°C				
6 – 316 Stainless Steel	2 – 0-185 psig 0-12.8 bar								
	3 – 0-300 psig 0-20.7 bar								
	4 – 0-375 psig 0-25.9 bar								